The Compton Effect

Introduction

Light is made up of (many) photons. "Photon" is the name given to the particle-like aspect of light's behavior (in addition to the wave-like behavior you have previously measured). In this experiment we will study the interaction between energetic photons and electrons called Compton effect, named after Arthur Holly Compton who received the Nobel Prize for physics in 1927 for its discovery. To create energetic photons, we use radioactive decay from unstable isotopes in the previous experiments. For relevant information, please review the Introduction to Nuclear Radiation.

Theory of the Compton Effect

Kinematics of the Compton Effect

The Compton effect is based on treating light as consisting of particles of a given energy related to the frequency of the light wave. In this context, the particle of light is given the name "photon". An energetic photon with energy of 0.1 MeV (million electron volts) or larger is also often referred to as a gamma ray. An MeV is an energy unit, equal to the kinetic energy an electron would gain by being accelerated through a voltage difference of 1 MV (10^6 volts). Photons whose energy is in the range of 0.1 to 100 keV are usually referred to as X-rays (1 keV = 10^{-3} of 1 MeV).

If a photon with energy E_0 strikes a stationary electron, as in Figure 1, then the energy of the scattered photon, E, depends on the scattering angle, Θ , that it makes with the direction of the incident photon according to the following equation:

$$\cos\Theta = 1 - m_e c^2 \left[\frac{1}{E} - \frac{1}{E_0}\right] \tag{1}$$

, where m_e is the mass of the electron and m_e $c^2 = 511$ keV = .511 MeV. In materials, electrons are not stationary, but if the initial kinetic energy of the electron is small compared to the energy of the incoming photon, Eqn. (1) will describe the situation well. This will be the case for gamma rays (E > 10⁵ eV) scattering off outer electrons of atoms (typical kinetic energy of a few eV).



Fig. 1: Schematic diagram of Compton Effect kinematics.

The derivation of this equation is based on applying special relativity and kinematics to the photon as a quantum of light, but in the form we use, requires little or no reference to the wave nature of light! It's all about energy of the electron and photon, and the angle of the outgoing photon compared to the initial direction.

1

The total energy of the electron E_e is the sum of its kinetic energy T_e and its rest energy m_ec^2 , i.e. $E_e = T_e + m_ec^2$. The total energy of the recoiling electron can be computed from energy conservation in the

reaction and is given by:

$$E_e = E_0 + m_e c^2 - E$$
(2)
$$T_e = E_0 - E$$
(3)

or equivalently:

Clearly the electron energy achieves its maximum value in this scattering where the photon has its minimum energy. The lowest energy for the scattered photon results when it is back-scattered, *i.e.*, it emerges at 180 degrees with respect to its original direction, in which case Eq. 1 shows that the incident energy *Eo* and *Emin*, the minimum scattered photon energies are related as:

$$\frac{1}{E_{min}} - \frac{1}{E_0} = \frac{2}{m_e c^2}$$
(4)

The Compton Edge

These formulas do not tell us the relative probability of the possible scattering angles (and, equivalently, the relative probability of various recoiling electron energies). In Figure 2 we plot the energy dependence.



Fig. 2: The relative probability of finding an electron with scaled kinetic energy $t = Te/m_ec^2 = (Ee/m_ec^2 - 1)$. This varies somewhat with Eo; Eo = .511 MeV for this plot.

The important thing to take away from this plot is the rise in the probability with increasing kinetic energy up to the kinematic limit, where it abruptly falls to zero. In our experiment we will be looking for this shape, referred to as the Compton edge.

We have chosen to plot this for an incident photon with energy equal to the rest mass of an electron, $Eo = .511 \text{ MeV} = m_e c^2$, but if we had chosen a different incident energy, the shape would be similar, just with a different end point. A more detailed explanation of how this plot was calculated is given in Appendix 3.

The Experiment

The Apparatus

The apparatus in this experiment consists of a NaI (Tl) crystal attached to a photo multiplier tube. The crystal is surrounded by a heavy lead ring, whose purpose is to shield it by absorbing stray radiation not arriving from directly below the crystal. While the Geiger counter is useful in indicating the presence of ionizing radiation, it cannot give us any information about its energy, it has low efficiency for counting gamma rays and it has somewhat poor time response. A class of counters that overcome these difficulties are scintillation counters in which the incident radiation creates photons in proportion to the energy it loses and then these photons are amplified with a photomultiplier and converted into a voltage pulse whose amplitude is proportional to the energy deposited. One of the best of this kind of counters is an inorganic crystal of NaI doped with Tl. Some of its properties are summarized in the table below:

Sodium Iodide Scintillator
3.67
2.59
4.5
4.8
41.4
250
410
1.85
40,000

The Radiation length and Moliere Radius are length scales associated with electromagnetic radiation. Electrons and photons deposit their energy in the NaI detector over a finite distance, not just at a single point. For high energy electrons (E >> a few MeV), for example, the Radiation length (longitudinal, *i.e.*, along the incident direction) is the distance in which an electron loses all but 1/e of its energy and the Moliere radius is the transverse radius containing about 90% of the energy. In this lab our sources have a few MeV or less in which case the radiation length and Moliere radius are even shorter, assuring us that the particles (electrons or photons) deposit their full energy in our detector. So the detector can capture all the energy—if the particle hits near enough to the center of the detector.

The decay time of a pulse is the time it takes to decay to 1/e of its original amplitude. Two pulses will not be confused if they come a few decay times (5 or 6) separated from one another.

The light created by energy deposition in the crystal is funneled by plastic light guides to the photocathode of a photomultiplier tube where it undergoes amplification on the way to being turned into a voltage pulse. Since the light collection process is not perfectly efficient (a typical number is 10%) and since a typical photocathode efficiency for converting photons into electrons is 25%, the 40,000 photons per MeV created in the crystal appear as about 1,000 electrons/MeV after the first stage of the photomultiplier tube. If the energy resolution of the detector were dominated by counting statistics only then we would expect a fractional resolution of $1/\sqrt{1000}$ or about 3% at 1 MeV. In practice, other effects tend to make this number somewhat larger.

Using the NaI detector

The photomultiplier tube amplifies the initial signal by creating cascades of new electrons at several stages in proportion to the number of incident electrons. Typical gains in PM tubes can be 10^6 or more. The gain of the tube is proportional to the high voltage applied and thus we must take care that the voltage is constant during a measurement.

After amplification in the photomultiplier, the signal undergoes some shaping and is fed to an analog-to-digital (ADC) converter residing in the PC. There it is turned into a number proportional to its amplitude, suitable for computer display and manipulation.

NaI can measure the energy deposition due to electrons or photons (which may be gamma rays or lowerenergy X-rays). This is a more sophisticated detector than the Geiger counter. Instead of just a count (on or PHY 192

off), the output of the NaI counter is a voltage pulse *proportional to the energy deposited in the counter*, which is fed into a Multi Channel Analyzer (MCA) box read by the PC. Thus you will record a spectrum of energies, where the output recorded by the MCA is calibrated to match the amount of energy deposited in the detector. The output is a histogram of counts vs "channel number" (= histogram bin number). An instruction manual comes with each device and computer (PC). You should take a part of the first laboratory session to become familiar with the operation of the detector and the PC with the MCA card. Learn how to record and erase spectra, how to store spectra on your disk and how to subtract background spectra from spectra containing interesting characteristics. You should also learn how to make hard copies of your plots for inclusion into your formal write-up. Below you will find basic instructions for using the MCA; in Appendix 2 you will find more detailed information about the MCA.

Calibration

Calibration is the process of turning the horizontal scale of the histogram ("channel number") into an energy scale in keV, by using the facts that a) the channel number is proportional to energy and b) certain features in the histogram occur at specific energies. We will rely on four lines as standards: (1) the photo-peak of the 661.6 keV gamma ray, which is the highest energy peak in the ¹³⁷Cs spectrum, (2) a smaller X-ray peak at 32 keV which is the characteristic Barium K X-ray emitted by the ¹³⁷Cs source, (3) the photo-peak of the 1.33 MeV gamma ray of the ⁶⁰Co source, and (4) the photo-peak of the 1.17 MeV gamma ray of the ⁶⁰Co source. The "photo-peaks" are caused by photons of specific energy being fully absorbed by the detector. Details of the Cs and Co spectra can be found in Appendix 1.

First use the ¹³⁷Cs source. Put the source near the top of the source holder. Use the AutoCalibrate feature to find an appropriate high voltage and amplifier gain. The result will place the photopeak at 662 keV (AutoCalibrate expects a Cs source!).

Next add the ⁶⁰Co source and take data with *both* sources side by side. You will probably find that the Co peaks (and 1300 keV) are not on scale. Go to Settings | Amp/HV/.. and lower the fine gain until the Co peaks are on scale (should find the Cs peak a bit below middle of x axis). To establish a new calibration (since you have changed the fine gain), you can utilize the above four known energy scales. First, select 'Uncalibrate' from the menu, and then perform 2-point or 3-point calibration procedure. You need to retrieve the channel numbers from the spectra that correspond to the known energy scales, which are input parameters (in pair) for performing the point calibration. A good calibration covers a broad range. Be sure to *check that all the four known energy values are accurately reflected in the spectra after the calibration!* From now on carefully refrain from changing the high voltage or gain. After calibration, the program gives energy corresponding to the cursor position instead of channel number. Check the energies by putting the cursor on your peaks. Save.

If you find these instructions too sketchy, refer to Appendix 2.

Measurements

General Overview

We will not measure the angular Compton scattering distribution given by the Klein-Nishina formula. That would need a very powerful source of gamma rays. The safe handling of these sources would not be practical in this laboratory setting. We will, however, measure the end point for Compton scattering which corresponds to the maximum kinetic energy that outgoing electrons obtain when the photon is back-scattered when its final direction is roughly 180 degrees from its incoming direction [see Eqn. (1)]. The outgoing electrons might come from the detector, or in other nearby materials—electrons are in all matter. We will also identify the backscattered photon peaks within the Compton plateau (see below). We will do these

measurements using first the ¹³⁷Cs source and then the ⁶⁰Co source, recalling that the former emits one photon and the latter two, at different energies.

The Compton Plateau

Measure the spectrum of the Cs source. Put it on a shelf just below the Nal detector. Choose a time sufficiently long so that statistics are not a problem. Save and print your spectrum in log scale (why?). Repeat for Co source. Do you need to perform background subtraction? If so, see detailed directions in Appendix 2.

On the spectra, label (as appropriate) the ¹³⁷Cs and ⁶⁰Co photo-peaks, the Barium X-ray, the Compton plateaus, and the Compton edge(s). Write the energy corresponding to each of these features next to the feature on the plot. Use the spectrum software to help with the energy measurements. Estimate your uncertainty in the peak position by trying to re-measure the peaks with the software. The Compton plateau should show up in your spectrum as a region of higher counting rate due to either electrons or photons in or near the most probable energy configurations, according to the theory of Compton scattering (remember that the detector measures photons or electrons equally well).

Questions) Calculate the expected energy of each Compton edge from Compton Effect kinematics using the gamma ray energies from ¹³⁷Cs and ⁶⁰Co. Use the calculations to identify the Compton edges on the plots and label them according to the photo-peak from which they originate. Are they consistent?

The Report

We will not have official report for this lab. At the end of the lab, turn in the spectra you obtain from ¹³⁷Cs and ⁶⁰Co sources. Label the Barium X-ray (only for ¹³⁷Cs), the Compton plateaus, and the Compton edge(s) on the spectra and answer the questions above in a separated sheet, indicating whether the obtained spectra agree with your calculations.



Appendix 1: Decay schemes for 60 Co and 137 Cs

The isotope notation ${}^{137}Cs_{55}$ indicates an isotope of Cesium (element 55, with 55 protons) which has 137-55=82 neutrons. Vertical arrows represent simple transitions from one nuclear energy level to another, which result in emission of a photon whose energy is equal to the difference in energy levels. The sloped arrows represent a beta decay which results in an electron and a neutrino being emitted. The beta electron does not have a fixed energy but rather a spectrum which has a maximum value; a typical value might be about half the maximum value.

The Cs sources we use have thin windows (for easier transmission of betas), while the Co sources do not have a beta window. Also the Co beta energy is much less than for Cs. Some details of the decays are given below:

⁶⁰Co: This isotope has a half life of 5.28 years and beta decays to the excited states of the stable nucleus of ⁶⁰Ni. In 99.9% of the cases the ⁶⁰Ni (2.51 MeV 4th excited state) is formed, with a maximum beta energy of 0.31 MeV. The excited state subsequently decays in less than 10^{-12} sec to the ground state via the emission of 2 photons, one with energy 1.17 MeV and one with 1.33 MeV.

137Cs: This isotope beta decays with a half-life of 30.0 years, with 93.5% of the decays creating 137 Ba in its 2nd excited state at 0.66 MeV and 6.5% creating 137 Ba in the ground state. The maximum beta energy is 0.52 MeV for the decay to the excited state, and 1.18 MeV for the decay directly to the ground state. The excited state has a half-life of 2.55 min. and decays 90% of the time through the emission of a 0.66 MeV photon and 10% of the time with the emission of an atomic conversion electron of a similar energy, equal to 0.66 MeV minus the binding energy. So 84% (= 0.935 * 0.90) of all beta decays of this isotope produce a photon in the final state.

Appendix 2: Multichannel Analyzer Detailed Instructions

Basic commands for software:

Turn on analyzer box's power switch **before** clicking on the little spectrum icon on the PC.

There may be issues with starting up the MCA after computers have been down for a while. Some computers claim to not find any such USB hardware, or that the USB is off, when it's not. Sometimes just trying again does the trick, or logging out and back in. Sometimes it requires a full reboot *with MCA power off*; once you were logged back in, turn the power on, and try again. At worst you may have to agree to install software: say Accept, Continue Anyway, etc through at least 2 cycles of install. Remember, you certainly need power on the box *before*clicking on the MCA icon.

You start in Live mode (see title bar).

Settings | Energy Calibration | Autocalibrate for Cs to do initial setup. Print and it will preserve settings.

Eraser Icon: deletes spectrum

Click Go and keep going till you like it, then Stop

to save spectrum File | Save

Go to Setting Amp/HV/ADC Settings. Write down the settings for high voltage, gain, and fine gain for future references (or Save Setup and later Load Setup to snag the settings you used later).

Timed spectrum: Settings | Presets | Live Time |then pick some big number like 1000 sec

Region of Interest Settings | ROI | Set ROI

Drag cursor from lower to upper region, fairly symmetrical around peak

Gives you total counts in peak, and calculates Centroid (peak) & full width at half-maximum

Can also do Settings | Presets |Integral Counts to run until desired counts in ROI

Ba X-ray: it may appear cut off or hard to see. If so, try the following: on the bottom of the x axis there are two little triangles. These are ULD and LLD (upper and lower discriminator level). The default LLD is 6%; lower it by clicking and dragging all the way to the left (0%).

Calibration

Don't be bothered by the report that the detector is at 500V after Autocalibrate: there is no strong reason for the NaI voltage to be the same as a GM voltage! The important issue is whether it puts the Cs peak at 662 keV like it should.

After confirming the detector and analyzer are functioning properly, now put *both* Cs and Co sources in the top drawer. Erase the old spectrum and click "Go" to start a new recording. You probably find that Co peak (at 1170 and 1330 keV) are not on scale. Autocalibrate doesn't work because it will put the Co gammas off scale (> 1024) after having put the Cs at channel 662. To proceed, first "uncalibrate". Go to Settings | Amp/HV/.. and lower the fine gain until the Co peaks are on scale.

Next do 2-point or 3-point calibration. Pick keV for units then click on peaks you choose, giving energy in keV for each peak. Be sure to check all four calibration points to see that they have good energies. If the energy at channel 0 is substantially different than 0 (more than \pm 10 keV), the calibration is dubious. This will almost certainly force you to pick Ba X-ray as one of the calibration points. The peak of the Pb X-ray is at the K alpha line. K alpha is a close-spaced doublet, usually the strongest of the K X-rays, from 2p to ground.

Save your spectra! Then you can go back and remeasure! But print in live mode to capture settings. Just print from the MCA program-no need to export to Kgraph or Excel.

Background subtraction

1) The software has the smarts to scale background by live time.

2) Procedure: save real and bkg spectrum via File | Save

File | Open (you are now in file mode—see Title bar; by default, same size as original screen!)

Open spectrum file

Then Strip Background | Load Background | open background file

Strip subtracts it. You can also display side by side.

For whatever reason, the term commonly used in Nuclear Physics for background subtraction is Stripping the Spectrum.

Appendix3: Some Details of the Compton Effect

The Klein-Nishina Angular Distribution Formula

While Equations 1-3 tell us how to compute the energies of the scattered photon and electron in terms of the photon's angle, they do not tell us anything about the likelihood of finding a scattered photon at one angle relative to another. For this we must analyze the scattering process in terms of the interactions of electrons and photons.

The electron-photon interaction in the Compton effect can be fully explained within the context of our theory of Quantum Electrodynamics or QED for short. QED is well beyond the scope of this course and we shall simply quote some results. We are interested particularly in the angular dependence of the scattering or the differential cross-section and the total cross-section both as a function of the energy of the incident photon. If you haven't seen the term "cross section" before, for now you can just think of it as a quantity proportional to the relative probability of an interaction with a particular value of the variables.

First we write the differential cross-section, also known as the Klein-Nishina formula:

$$\frac{d\sigma}{d\Omega} = \frac{\frac{1}{2}r_o^2 [1 + \cos^2 \Theta]}{[1 + 2\varepsilon \sin^2 \Theta/2]^2} \left\{ 1 + \frac{4\varepsilon^2 \sin^4 \Theta/2}{[1 + \cos^2 \Theta] [1 + 2\varepsilon \sin^2 \Theta/2]} \right\}$$
(5)

where $\varepsilon = E_0/m_ec^2$ and r_0 is the "classical radius of the electron" defined as e^2/m_ec^2 and equal to about 2.8 x 10⁻¹³ cm. The formula gives the probability of scattering a photon (integrated over φ) into the solid angle element $d\Omega = 2\pi |d (\cos \Theta)| = 2\pi |\sin \Theta| d\Theta$ when the incident energy is E_0 . We illustrate this angular dependence in Figure 3 for one particular photon energy.



Note that the most likely scattering is in the forward direction (θ =0) and that the probability of scattering backward (θ near π) is relatively constant with angle. This shape varies mildly with the initial photon energy E; here we chose Eo= m_ec² = .511 MeV.

Since we will be measuring energy, it is of interest to rewrite this to give the probability of measuring electrons with a given kinetic energy $T = E_e - m_e c^2$. We can get the expression plotted in figure 2 by

substituting for the angle Θ in Eq. (5) via Equations (2) and (3), and then using the solid angle definition given below Eq. (5), and applying the relationship:

$$\frac{d\sigma}{dT_e} = \frac{d\sigma}{d\Omega} \cdot \frac{d\Omega}{dT_e} = \frac{d\sigma}{d\Omega} \cdot \frac{2\pi m_e c^2}{(E_o - T_e)^2} = \frac{d\sigma}{d\Omega} \cdot \frac{2\pi}{m_e c^2 (\varepsilon - t)^2} \tag{6}$$

The final form on the right uses the definitions $\varepsilon = E_0/m_ec^2$ and $t = T_e / m_ec^2$. Energy dependence

The Klein-Nishina formula can be integrated over photon scattering angle (or electron recoil energy) to yield the total cross-section, which displays the dependence on the incident energy (shown in Fig 4) for the Compton process:



Fig. 4: Energy dependence of Compton scattering, vs. $x = \varepsilon = Eo/m_ec^2$.

The Compton process is weakly energy dependent up until about .1 MeV, when it begins to decrease significantly; other processes become more important at higher energies.