



Layout



M 2:1



Masse nur informativ,
keine Prüfpläne erstellen.



Technical Data:

Insertion/withdrawal force per contact:	≤ 10N / ≤ 1.6N
Mechanical operations:	≥ 500
Contact resistance:	≤ 1 mOhm
Operation Temperature:	-55°C - +125°C
Solder temperature:	according JEDEC 020C
Suitable assembly process:	leadfree wave / reflow soldering
RoHS compliance:	yes (6/6)
Designed for use with:	right angle female 2mm HM connector
Packaging:	antistatic plastic bag
Packaging unit:	100 pieces per bag
Marking of packaging:	label or direct printed on bag required date see ERNI labeling spec. 254792
Current capacity:	40 A

Missing informations
and dimensions
see at DIN 41626

053298	1	2 - 4 µm NiP+, 0.15 µm Au
284924	1	2 - 3 µm Ni, min. 1.3 µm Au
Part-No.	Class	Plating

Copyright by ERNI GmbH.
Proprietary notice pursuant to ISO 16016 to be observed.

Information:		Tolerances		Scale	5:1
All rights reserved. Only for Information. To ensure that this is the latest version of this drawing, please contact one of the ERNI companies before using.		Subject to modification without prior notice. Drawing will not be updated.		Designation	
		www.ERNI.com		High Current Female Contact <i>Right Angle Solder Termination</i>	
G	19.08.2008			284923	1
Index	Date			Class	A3
				Class	STVSKO