L2 Header

- **B**0 # objects (NOT IN HEADER)
- Header Length in 4B words (1B) **B1**
- Object Length in 4B words (1B) B2
- Header/Trailer Format # (hi 3 bits) [ONLY changes if new format] B3 Object Format # (lo 5 bits)
- Data Type # (1B) **B**4
- **B**5 Bunch # (1B)
- B6-7 Rotation# (2B)
- Algorithm Major Version (1 B) **B**8
- Algorithm Minor Version (1B) **B**9 or Processor Specific Bits (1B)
- Processor Specific Bits (1B) B10
- **Status** Bits B11

- [note 255 max!] [=3 for default]
- [ALL same size!]
- [ONLY changes if new format] [unique in all L2 MBT inputs]

[B6 is LSB of rotation] [e.g. 7 from Version 7.1] [e.g. 1 from 7.1] [esp. if hardware data source]

[b7 on means some error] [some standard for L2 Proc]

Michigan State University

Standard Status Bits b7, b0 for all; others if L2proc

- 7 error on event (any kind): use at own risk
- 6 no processing attempted (none required)
- 5 object list truncated (any reason)
- 4 Receiver error on some input physical trailer
- 3
- 2
- 1 more data-type info (processor-specific) other test modes; unbiased-sample data...
- 0 0 for real data, 1 for MC data

L2 Trailer

B0 Bunch # (1B) = B5 of Header
B1 Data Type # (1B) = B4 of Header
(Swapped even/odd from Header)
B2 Longitudinal Parity of even Bytes
B3 Longitudinal Parity of odd Bytes
or--if parity too slow to calculate, Turn # (B6-7 of Header)
MBT Out, SLIC, FIC will append physical trailer with 8-bit hardware-generated longitudinal parity

Zero padding to 16 B group FOLLOWS trailer, before End of Event

L2 Physical Trailer

• FIC, SLIC, MBT Out: add a physical 2B trailer

- after logical trailer, before End Event
 - This BREAKS 16B boundary, but handled by MBT
- B0 8 bit longitudinal parity of received data
- B1 Status Bits [b7 on if any receive error]
 - not included longitudinal parity!

- b0, b1 are type ID: 0 = FIC, 1 = SLIC, 2 = MBT

• MBT inputs place this in B0, B1 of 16B physical trailer

- adds B14, its own longitudinal parity of everything received
- B15 its own Error Bits [b7 on if any receive error]
- reserves 4B for incoming, may give error locations in B4-13
- MBT Outs produce 2B physical trailer like FIC

Michigan State University